

φ250 | EC 无蜗壳风机

Plug Fan With Support Bracket And Plate

Plug Fan With Support Bracket And Plate




产品特征 Product Characteristic



风轮材料: 铝板
 旋转方向: 逆时针
 保护等级: IP54
 绝缘等级: F
 电机工作制: S1连续工作制
 轴承: 免维护深沟球轴承
 工作环境温度: -25℃~+50℃
 工作电压: 200V~277V/1P
 内部集成控制器
 0~10V PWM控制

Impeller Material: Sheet Aluminium
 Rotation: CCW, seen on LE
 Type of Protection: IP54
 Insulation Class: F
 Mode of Operation: S1
 Bearings: Maintenance-free ball bearings
 Perm.amb.temp.: -25℃~+50℃
 Operating Voltage: 200V~277V/1P
 Controller Integrated
 0~10V PWM Control

Flow Rate Curve



n (r/min)	Pst (Pa)	P1 (W)	I (A)	ActualEFF (%)	Erp2015 (%)
3100	0	354	1.55		
3100	300	446	1.94		
3100	600	536	2.29	58.7	48.6
3100	750	520	2.27		



技术参数表 Technical Parameter

型号 Model	电压 Voltage (VAC)	频率 Frequency (Hz)	输入功率 Input Power (W)	电流 Current (A)	风量 Air Volume (m³/h)	转速 Speed (r/min)	噪音 Noise [dB(A)]	重量 Weight (Kg)
ECF(K)6E250-PLHDAL4	230	50/60	536	2.3	2600	3100	74	9.7