

# φ250


## EC 无蜗壳风机

### Plug Fan With Support Bracket And Plate

Plug Fan With Support Bracket And Plate



Flow Rate Curve





### 产品特点 Product Characteristic

风轮材料: 铝板  
 旋转方向: 逆时针  
 保护等级: IP54  
 绝缘等级: F  
 电机工作制: S1连续工作制  
 轴承: 免维护深沟球轴承  
 工作环境温度: -25℃~+50℃  
 工作电压: 200V~277V/1P  
 内部集成控制器  
 0~10V PWM控制

Impeller Material: Sheet Aluminium  
 Rotation: CCW, seen on LE  
 Type of Protection: IP54  
 Insulation Class: F  
 Mode of Operation: S1  
 Bearings: Maintenance-free ball bearings  
 Perm.amb.temp.: -25℃~+50℃  
 Operating Voltage: 200V~277V/1P  
 Controller Integrated  
 0~10V PWM Control

n (r/min)	P <sub>et</sub> (Pa)	P <sub>1</sub> (W)	I (A)	ActualEFF (%)	Erp2015 (%)
3540	0	661	2.88		
3540	400	741	3.24		
3530	800	803	3.47	54.3	50.5
3530	1100	509	2.26		



### 技术参数表 Technical Parameter

型号 Model	电压 Voltage (VAC)	频率 Frequency (Hz)	输入功率 Input Power (W)	电流 Current (A)	风量 Air Volume (m³/h)	转速 Speed (r/min)	噪音 Noise [dB(A)]	重量 Weight (Kg)
ECF(K)6E250-PLHDAL10	230	50/60	803	3.47	2850	3530	75	11.7