

Plug Fan With Support Bracket And Plate




产品特点 Product Characteristic



风轮材料: 铝板
 旋转方向: 逆时针
 保护等级: IP54
 绝缘等级: F
 电机工作制: S1连续工作制
 轴承: 免维护深沟球轴承
 工作环境温度: -25℃~+50℃
 工作电压: 200V~277V/1P
 内部集成控制器
 0~10V PWM控制

Impeller Material: Sheet Aluminium
 Rotation: CCW, seen on LE
 Type of Protection: IP54
 Insulation Class: F
 Mode of Operation: S1
 Bearings: Maintenance-free ball bearings
 Perm.amb.temp.: -25℃~+50℃
 Operating Voltage: 200V~277V/1P
 Controller Integrated
 0~10V PWM Control

Flow Rate Curve



| n (r/min) | Pet (Pa) | P1 (W) | I (A) | ActualEFF (%) | Erp2015 (%) |
|-----------|----------|--------|-------|---------------|-------------|
| 1630 | 0 | 206 | 1.72 | | |
| 1624 | 150 | 283 | 2.24 | | |
| 1540 | 300 | 276 | 2.18 | 47.3 | 45.6 |
| 1620 | 390 | 289 | 2.30 | | |



技术参数表 Technical Parameter

| 型号 Model | 电压 Voltage (VAC) | 频率 Frequency (Hz) | 输入功率 Input Power (W) | 电流 Current (A) | 风量 Air Volume (m³/h) | 转速 Speed (r/min) | 噪音 Noise [dB(A)] | 重量 Weight (Kg) |
|---------------------|------------------|-------------------|----------------------|----------------|----------------------|------------------|------------------|----------------|
| ECF(K)6E355-PLHDAL2 | 230 | 50/60 | 270 | 2.3 | 2700 | 1550 | 70 | 14 |