

φ400 | EC 无蜗壳风机


Plug Fan With Support Bracket And Plate

Plug Fan With Support Bracket And Plate





产品特征 Product Characteristic

风轮材料: 铝板	Impeller Material: Sheet Aluminium
旋转方向: 逆时针	Rotation: CCW, seen on LE
保护等级: IP54	Type of Protection: IP54
绝缘等级: F	Insulation Class: F
电机工作制: S1连续工作制	Mode of Operation: S1
轴承: 免维护深沟球轴承	Bearings: Maintenance-free ball bearings
工作环境温度: -25℃~+50℃	Perm.amb.temp.: -25℃~+50℃
工作电压: 380V~480V/3P	Operating Voltage: 380V~480V/3P
内部集成控制器	Controller Integrated
0~10V PWM控制	0~10V PWM Control



n (r/min)	Pst (Pa)	P1 (W)	I (A)	ActualEFF (%)	Erp2015 (%)
2410	0	1703	2.72		
2248	300	1701	2.73		
2136	700	1687	2.69	55.5	53.9
3500	1000	1699	2.71		



技术参数表 Technical Parameter

型号 Model	电压 Voltage (VAC)	频率 Frequency (Hz)	输入功率 Input Power (W)	电流 Current (A)	风量 Air Volume (m³/h)	转速 Speed (r/min)	噪音 Noise [dB(A)]	重量 Weight (Kg)
ECF(K)8D400-PLHDAL3	400	50/60	1700	2.7	8300	2400	77	21.5