

φ400


EC 无蜗壳风机

Plug Fan With Support Bracket And Plate

Plug Fan With Support Bracket And Plate





Flow Rate Curve



产品特点 Product Characteristic

- | | |
|--------------------|--|
| 风轮材料: 铝板 | Impeller Material: Sheet Aluminium |
| 旋转方向: 逆时针 | Rotation: CCW, seen on LE |
| 保护等级: IP54 | Type of Protection: IP54 |
| 绝缘等级: F | Insulation Class: F |
| 电机工作制: S1连续工作制 | Mode of Operation: S1 |
| 轴承: 免维护深沟球轴承 | Bearings: Maintenance-free ball bearings |
| 工作环境温度: -25℃~+50℃ | Perm.amb.temp.: -25℃~+50℃ |
| 工作电压: 200V~277V/1P | Operating Voltage: 200V~277V/1P |
| 内部集成控制器 | Controller Integrated |
| 0~10V PWM控制 | 0~10V PWM Control |

n (r/min)	P _{st} (Pa)	P ₁ (W)	I (A)	ActualEFF (%)	Erp2015 (%)
1500	0	411	3.61		
1508	150	493	4.10		
1438	350	491	4.14	49	48.3
1497	450	500	4.03		



技术参数表 Technical Parameter

型号 Model	电压 Voltage (VAC)	频率 Frequency (Hz)	输入功率 Input Power (W)	电流 Current (A)	风量 Air Volume (m³/h)	转速 Speed (r/min)	噪音 Noise [dB(A)]	重量 Weight (Kg)
ECF(K)8E400-PLHDAL0	230	50/60	490	4.15	4500	1500	75	14.5